


1		2			3		4		5		6	
产品代号 Part code	产品料号 Part NO.	重量/Weight		线径/Wire Gauge		d	D	剥线长度 Stripping length				
		g	mm ²	AWG								
CEM-1.0R	20080001010	1.29	1.0	18	1.45	2.6	7.5					
CEM-1.5R	20080001015	1.33	1.5	16	1.75	3.0	7.5					
CEM-2.5R	20080001025	1.37	2.5	14	2.25	3.5	7.5					




技术参数:

- 材料: 铜合金
 - 表面处理: 镀银
 - 额定电流: 16A
 - 接触电阻: ≤1mΩ
 - 线径范围: 1.0-2.5mm²(18-14 AWG)
- 延迟加长针较短, 延迟接触, 起保护电路避免电弧

Technical specification:

- Material: copper alloy
 - Surface: hard-silver plated
 - Rated current: 16A
 - Contact resistance: ≤1mΩ
 - Wire gauge: 1.0-2.5mm²(18-14 AWG)
- Delay pin is relatively short, delay contact, protect circuit to avoid electric arc.



						表面处理 Finish		-		图号 Drawing No.		-		
						材料 Material		-		产品代号 Part Code		CEM-XXR		
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date					产品料号 Part No.		-	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name		-		
绘图 Drawn		18.10.2010	标准化 Stand.	-	-	2:1	V1.0	-	-					
审核 Checked		18.10.2010												
工艺 Process	-	-	批准 Approved		18.10.2010			All Dimensions in mm Original Size DIN A 4				浙江西霸士电气有限公司		