



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M25
- 联锁元件:
 - 锁扣方式: 双扣
 - 材料: 不锈钢+软胶

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M25
- Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR

| | | | | | | | | | | | | | |
|---------------|--------------|------------------|------------|-----------------|------------|---|------|------------|--------------|-------------------|-----------------------|---------------|------------|
| | | | | | | 表面处理 Finish | | - | | 图号 Drawing No. | | - | |
| | | | | | | 材料 Material | | - | | 产品代号 Part Code | | H10B-TGBH-M25 | |
| 标记 Mark | 次数 Number | 变更描述/Description | | 姓名 Signature | 日期 Date | 比例 Scale | | 版本 REV. | 重量 Weight | 数量 Qty. | 产品料号 Part No. | | 1280100125 |
| 绘图 Drawn | | 姓名/Name | 日期/Date | 姓名/Name | 日期/Date | 1:2 | V1.0 | | | | 产品名称 Part Name | | - |
| 审核 Checked | | | 18.10.2010 | | | | | | | | 产品标准 Part Standard | | - |
| 工艺 Process | | | | 批准 Approved | 18.10.2010 | All Dimensions in mm Original Size DIN A 4 | | | | 浙江西霸士电气有限公司 | | | |